CLAIMS

- 1. A fluid-dispenser member (1) comprising:
 - · a body (10) defining an inlet duct (11);
- · an actuator rod (13) that is displaceable in the
- 5 body;

10

7

1

- \cdot an actuator member (15) coupled to the actuator rod;
- · fastener means (17) for fastening the body (10) in an opening (20) of a receptacle (2) containing a fluid;
- an ID unit (3) capable of supplying information relating to the dispenser member,

the dispenser member being characterized in that said ID unit (3) is housed in a gap defined between the

- body (10) and the fastener means (17), said gap (19) forming an annular housing defined by the body (10), by a portion (170) of the fastener means (17), and by the neck gasket (18).
- 20 2. A dispenser member according to claim 1, in which said gap (19) is defined by a neck gasket (18) disposed around the body, and designed to be compressed against the opening (20).
- 25 3. A fluid-dispenser member according to claim 1 or claim 2, in which said portion (170) is engaged below a rim (12) formed by the body.
- 4. A dispenser member according to claim 1, in which the
 30 ID unit (3) comprises an integrated circuit (301), and an antenna (302) capable of transmitting signals carrying information.
- 5. A dispenser member according to any preceding claim, in which the ID unit (3) is fastened to the body (10).

AMENDED SHEET

6. A dispenser member according to claim 4, in which the ID unit (3) includes a substrate (303) in or on which the integrated circuit (301) and the antenna (302) are disposed.

5

- 7. A dispenser member according to any preceding claim, in which the fastener means comprise a ring for crimping, screw-fastening, snap-fastening, or force-fitting.
- 10 8. A fluid dispenser comprising a receptacle (2) and a dispenser member (1) according to any preceding claim.